

SECTION 09 65 00

RESILIENT FLOORING

This document is intended to note the Owners Design Requirements (ODR) for the titled specification section. Design professional to review and integrate ODR into the project's technical specifications. This ODR document should not be viewed as a standalone technical specification.

PART 1 - GENERAL REQUIREMENTS

- ◆ EXTRA MATERIALS
 - Provide ten (10) cartons of each material specified.
- ◆ WARRANTY
 - Furnish manufacturer's standard warranty for products specified.

PART 2 - PRODUCTS AND MATERIALS

- ◆ TILE FLOORING
 - Manufacturers:
 - Roppe
 - Johnsonite
 - Armstrong
 - Resilient Tile: ASTM F1066; Class 2
 - Size: 12x12
 - Nominal Thickness: 1/8".
 - Style: Solid color as specified on Drawings.
 - PVC-free.
 - Backing: Smooth factory-sanded.
- ◆ ACCESSORIES
 - Manufacturer:
 - Johnsonite
 - Primers and Adhesives: Waterproof; types recommended by flooring manufacturer.
 - Interior Adhesives: Maximum volatile organic compound content in accordance with SCAQMD Rule 1168.
 - Sealer: Type recommended by flooring manufacturer.
 - Rubber Transition:
 - Black color.
 - Use profile to accommodate installation and taper to meet abutting material without a tripping hazard. EG or CTA profile for carpet to VCT. CD profile for VCT to VCT.

PART 3 - EXECUTION

N/A

END OF SECTION