

SECTION 09 30 13

CERAMIC TILING

This document is intended to note the Owners Design Requirements (ODR) for the titled specification section. Design professional to review and integrate ODR into the project's technical specifications. This ODR document should not be viewed as a standalone technical specification.

PART 1 - GENERAL REQUIREMENTS

N/A

PART 2 - PRODUCTS AND MATERIALS

◆ TILE PRODUCTS

- Ceramic Tile Type CWT-1: Porcelain tile.
 - Manufacturers:
 - Arizona Tile
 - Ermosa.
 - Module Size: 12 by 24 inches.
 - Thickness: 3/8 inch (8 mm).
 - Finish: Bright, opaque glaze.

◆ Ceramic Tile Type CWT-2: Accent tile.

- Manufacturers: Subject to compliance with requirements, provide products by the following:
 - Stone Source
 - MetaPlus Mosaic
 - Customer Blend.
- Module Size: 20mm.
- Thickness: 3/8 inch (8 mm).
- Finish: Bright, opaque glaze.

◆ SETTING MATERIALS

- Improved Modified Dry-Set Mortar (Thinset): ANSI A118.15.
 - Provide prepackaged, dry-mortar mix containing dry, re-dispersible, vinyl acetate or acrylic additive to which only water must be added at Project site.
 - Provide pre-packaged, dry-mortar mix combined with acrylic resin liquid-latex additive at Project site.
 - For wall applications, provide mortar that complies with requirements for non-sagging mortar.

◆ GROUT MATERIALS

- High-Performance Tile Grout: ANSI A118.7.
 - Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - LATICRETE SUPERCAP, LLC.
 - TEC / H.B. Fuller Construction Products Inc.

PART 3 - EXECUTION

N/A

END OF SECTION