

SECTION 10 21 13

TOILET COMPARTMENTS

This document is intended to note the Owners Design Requirements (ODR) for the titled specification section. Design professional to review and integrate ODR into the project's technical specifications. This ODR document should not be viewed as a standalone technical specification.

PART 1 - GENERAL REQUIREMENTS

N/A

PART 2 - PRODUCTS AND MATERIALS

- ◆ MANUFACTURER
 - Bobrick
 - COMTEC (hinges)
- ◆ PRODUCTS
 - Bobrick Partitions: 1080 Duraline Series ceiling hung with institutional hardware
 - Do not use the institutional spring-loaded continuous piano hinge provided by BOBRICK, use a helix hinge by "COMTEC".
- ◆ MATERIALS
 - Solid Phenolic
 - Denim Blue (bobrick)
 - Hardware: Type 304 stainless steel with satin finish. Continuous piano helix hinge by "COMTEC", gravity type.
- ◆ FABRICATION
 - Fabricate components for ceiling hung installation: Overhead Cross Bracing: 3/4" x 6" Solid Phenolic installed at 6'-10" A.F.F.
 - Toilet Compartment Doors and Panels: Stalls shall be a minimum of 6'-0" depth.
 - Urinal Screens: 1/2 inch by 24 inches wall mounted with a **three** wall panel brackets.
 - Provide a 2 inch by 3 inch metal engraved tag for each toilet and urinal partition listing the stall and urinal number. (Coordinate with Owner for numbering).

PART 3 - EXECUTION

N/A

END OF SECTION